



## Description

61 and 61A are composed of Dacron and Glass woven fabric impregnated with a high quality electrical insulating varnish. 61 A has a thermosetting acrylic pressure sensitive adhesive applied to one side. Both tapes have excellent flexibility and elongation. They have high dielectric strength, conforms tightly to irregular shapes and surfaces.

## Recommended Uses

Both tapes are excellent for use in motor coils, lead wires, layer insulation in small transformers, and electrical maintenance work.

## Specifications

PROPERTY	VALUE	UNIT	TEST METHOD
	<b>61</b>	<b>61A</b>	
<b>PHYSICAL</b>			
Color	dry tan	w/adhesive tan	-
Thickness	0.007	0.008	inch
Tensile Strength	40	40	lb/in
Elongation			
@10lb	2.5	2.5	%
@15lb	6.0	6.0	%
Adhesion	-	2.0	lb/in
Operating Temp	155	155	°C
Emergency Overload	185	185	°C
<b>ELECTRICAL</b>			
Dielectric Strength	1300	1300	v/mil

Data in table represent average test results and are not to be used for specification purposes. The product user should make his/her own tests to determine the product's suitability for the intended use.

## Features

- Straight weave with bias characteristics.
- Exceptionally high dielectric strength.
- Retains dielectric strength on heat aging.
- Excellent flexibility and conforms well to irregular shapes.
- High tensile and edge-tear strength.
- Meet requirements for Class F insulation.

## Sizes

- 3/4 in. x 60 ft.  
19mm x 20m
- 1 1/2 in. x 108 ft.  
38mm x 33m

Other sizes available upon request

**LIMITED WARRANTY:** Plymouth warrants that its Product will substantially conform to that products written specifications exclusively contained in its Plymouth product data sheet for a period of one (1) year from the date of shipment. (Unless provided otherwise in product's data sheet). Plymouth makes no warranty to the distributor, its customers, or the product's end user for the products merchantability and/or suitability for his/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proved to be defective within the terms described above, and provided buyer shall have first complied with all return policies of Plymouth, PLYMOUTH'S SOLE OBLIGATION AND BUYER'S EXCLUSIVE REMEDY UNDER THIS PRODUCT WARRANTY SHALL BE TO REPLACE SUCH QUANTITY OF THE PRODUCT AS IS PROVED TO BE DEFECTIVE WITHIN THE TIME PERIOD SPECIFIED ABOVE. EXCEPT AS EXPRESSLY SET FORTH HEREIN, PLYMOUTH MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED. In no event shall Plymouth be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products. (rev. 1/95)

Plymouth is a registered trademarks of Plymouth Rubber Company, Inc.